

**Adapter :**

**Applications :**

- CATV
- Telecommunication networks
- Test equipment
- Metro
- Multimedia
- DATA networks
- Video
- FTTX



**Specifications :**

Parameter	FC, ST		SC, LC, E2000		MPO	
	Singlemode	Multimode	Singlemode	Multimode	Singlemode	Multimode
Insertion Loss	≤ 0.2 dB	≤ 0.2 dB	≤ 0.2 dB	≤ 0.2 dB	≤ 0.2 dB	≤ 0.2 dB
Mating Durability 500 times	< 0.2 dB	< 0.2 dB	< 0.2 dB	< 0.2 dB	N/A	N/A
Operation Temperature	-40 to +75 °C	-40 to +75 °C	-40 to +75 °C	-40 to +75 °C	-25 to +70 °C	-25 to +70 °C
<b>Material :</b>						
Body	Zinc-Alloy	Zinc-Alloy	PBT	PBT	Polyetherimide	Polyetherimide
Sleeve	Ceramic (ZrO <sub>2</sub> )	Phosphor Bronze (PB)	Ceramic (ZrO <sub>2</sub> )	Ceramic (ZrO <sub>2</sub> )	N/A	N/A

**Ordering Information :**

P/N	Descriptions
AD11SS-D14C	Adapter FC D-Hole 14 Ceramic
AD11ASS-D	Adapter FCA D-Hole Ceramic
AD12SS-C	Adapter SC SM Simplex
AD12ASS-C	Adapter SCA SM Simplex
AD12SS-C-NF	Adapter SC SM Simplex w/o Flange
AD12ASS-C-NF	Adapter SCA SM Simplex w/o Flange
AD12MS	Adapter SC MM Simplex
AD13SS-C	Adapter ST SM Ceramic
AD14SD-F	Adapter LC SM Duplex SCF
AD14SD-NF	Adapter LC SM Duplex SCF w/o Flange
AD14ASD-F	Adapter LCA SM Duplex SCF
AD14MD-F	Adapter LC MM Duplex SCF
AD14MD-NF	Adapter LC MM Duplex SCF w/o Flange
AD14MD-F-AQ	Adapter LC MM Duplex SCF Aqua
AD20SS-KUD	Adapter MPO Key Up/Key Down
AD20SS-KUU	Adapter MPO Key Up/Key UP



SC Simplex Adapter



SC Duplex Adapter