



Applications :

- CATV
- Telecommunication networks
- Active device termination
- Metro
- Local Area Networks (LANs)
- Data processing network
- Test equipment
- Premise installations
- Wide Area Networks (WANs)
- FTTX

Features :

- Low insertion loss and back reflection loss
- Good exchangeability
- Good durability
- High temperature stability
- Standard : Telcordia GR-326-CORE, ITU-T

Availability :

- Simplex/Duplex patch cord available
- Various boot (Cable) size available

Specifications :

Parameter	Singlemode	Multimode
Insertion Loss	UPC ≤ 0.2 dB, APC ≤ 0.3 dB	≤ 0.3 dB
Return Loss	UPC ≥ 50 dB, APC ≥ 60 dB	N/A
Fiber Type	G.652D, G.655, G.657A2, G.657B3	OM1, OM2, OM3, OM4, OM5
Fiber Core/Cladding	9/125 μm	62.5/125 μm, 50/125 μm
Polishing Grade	UPC, APC	UPC
Wavelength	1310/1550 nm	850/1310 nm
Repeatability	≤ 0.1 dB	
Durability	≤ 0.2 dB typical change, 500 matings	
Interchangeability	≤ 0.2 dB	
Tensile Strength	> 10 kg	
Cable Diameter	0.9, 2.0, 2.4, 3.0 mm	
Cable Jacket	PVC, LSZH (Low Smoke Zero Halogen)	
Operation Temperature	-40 to +75°C	



Example Connector Type

- 1 = FC
- 2 = SC
- 3 = ST
- 4 = LC
- 5 = E2000

■ Cable Diameter,
0.9 = 0.9 mm, 1.8 = 1.8 mm, 2 = 2.0 mm, 3 = 3.0 mm, 3.5 = 3.5 mm
Cable Length,
Length Unit, C = Centimeter, M = Meter Ex. C15 = 15 cm., M20 = 20 m.

■ Cable Type, 1 = SX-SX, 2 = DX-DX without Clip, 3 = DX-DX with Clip

■ Patch Cord, XX = Connector Type Code, YY = Polishing Type Code, Z = Fiber Type
Polishing Type Code, U = UPC Polishing, A = APC
UU = UPC/UPC, UA = UPC/APC, AU = APC/UPC, AA = APC/APC
Fiber Type, 1 = MM OM1, 2 = MM OM2, 3 = MM OM3, 4 = MM OM4, 5 = SM G.652D, 6 = SM G.657A2

Ordering Information :

P/N	Descriptions
PA33UU6-2-2M5	Patch Cord ST/ST SM G657A2 DX2 LS 5M
PA33UU6-1-2M5	Patch Cord ST/ST SM G657A2 SX2 LS 5M
PA33UU6-1-3M5	Patch Cord ST/ST SM G657A2 SX3 LS 5M
PA33UU5-1-2M5	Patch Cord ST/ST SM SX2 LS 5M
PA33UU3-2-2M5	Patch Cord ST/ST MM OM3 DX2 LS 5M
PA33UU3-1-2M5	Patch Cord ST/ST MM OM3 SX2 LS 5M

Connector Type ST = ST UPC, Cable Type SM = Singlemode Fiber, MM = Multimode Fiber
DX2 = Duplex 2.0 mm. Cable, DX3 = Duplex 3.0 mm. Cable, SX2 = Simplex 2.0 mm. Cable, SX3 = Simplex 3.0 mm. Cable, LSZH = Low Smoke Zero Halogen