

ODF RACK MOUNT 6-36 FIBERS 1U SLIDE WITHOUT DRAWER

ECO Series



P/N : ODFRO3S1U

Applications :

- Interface and distribute the fiber optical communication system

Features :

- Steel cabinet slide rack mount without drawer
- Cabinet made from electro galvanize steel 1.2 mm thickness
- Combine splicing function, storing of fiber optical cable, patch cord and pigtail
- Store and protect excess optical cable and patch cord
- Support FC/SC/ST/LC/E2000/MPO adapter type with 3 mini-snap plate
- Splicing and distribution 12 fibers or 24 fibers per tray
- Nice shape, easy installment and maintenance
- Easily fixed by cage nut on 19"/21" standard rack, convenient for operation and inspection
- Light gray cabinet
- Accept custom design and special order

Standard :

- Manufactured by ISO 9001-2015 company

Accessories :

- Cage nut, cable tie and cable gland
- Adapter, pigtail, splice tray and fusion sleeve as optional

Adapter Capacity :

- FC/SC/ST/E2000 adapter type support 18 fibers for 6 FC or SC mini-snap plate and 36 fibers for 12 FC or SC mini-snap plate
- LC (SCF) adapter type support 36 fibers for 6 SC mini-snap plate
- MPO adapter type support 18 ports for 6 MPO mini-snap plate

Dimensions :

- 440 W x 255 D x 44 H mm

Ordering Information :

P/N	Descriptions
ODFRO3S1U	ODF Rack Mount 36F (6-36F) 1U Slide without Drawer, 3 Mini-Snap Plate, Size 440x255x44 mm

ODF RACK MOUNT 6-24 FIBERS 1U SLIDE WITH DRAWER



P/N : ODFRDS1U



Applications :

- Interface and distribute the fiber optical communication system

Features :

- Steel cabinet slide rack mount with drawer
- Cabinet made from electro galvanize steel 1.2 mm thickness
- Combine splicing function, storing of fiber optical cable, patch cord and pigtail
- Store and protect excess optical cable and patch cord
- Support FC/SC/ST/LC/E2000 and MPO adapter type with 2 snap plate
- Splicing and distribution 12 fibers or 24 fibers per tray
- Clip-lock front cover, nice shape, easy installment and maintenance
- Easily fixed by cage nut on 19"/21" standard rack, convenient for operation and inspection
- Light gray cabinet
- Aluminum rack mount as optional
- Accept custom design and special order

Standard :

- Manufactured by ISO 9001-2015 company

Accessories :

- Cage nut, cable tie and cable gland
- Adapter, pigtail, splice tray and fusion sleeve as optional

Adapter Capacity :

- FC/SC/ST/E2000 adapter type support 12 fibers for 6 FC or SC snap plate and 24 fibers for 12 FC or SC snap plate
- LC (SCF) adapter type support 24 fibers for 6 SC snap plate and 48 fibers for 12 SC snap plate
- MPO adapter type support 12 ports for 6 MPO snap plate

Dimensions :

- 440 W x 310 D x 44 H mm (1U)
- 440 W x 310 D x 66 H mm (1.5U)

Ordering Information :

P/N	Descriptions
ODFRDS1U	ODF Rack Mount 24F (6-24F) 1U Slide with Drawer, Front Cover Flat Type, 2 Snap Plate, Size 440x310x44 mm
ODFRDS1.5U	ODF Rack Mount 24F (6-24F) 1.5U Slide with Drawer, Front Cover Flat Type, Size 440x310x66 mm