

# ODF MINI WALL MOUNT INDOOR 6-12 FIBERS



P/N : ODFWIS12U

#### Applications :

- Interface and distribute the fiber optical communication system

#### Features :

- Steel cabinet wall mount for indoor application
- Cabinet made from electro galvanize steel 0.8 mm thickness
- Combine splicing function, storing of fiber optical cable, patch cord and pigtail
- Store and protect excess optical cable and patch cord
- Support FC/SC/ST/LC adapter type with snap plate
- Splicing and distribution 12 fibers per mini-splice tray
- Nice shape, easy installment and maintenance
- Easily fixed by swell bolt, convenient for operation and inspection
- Provide strength member holder to fix the main fiber cable
- Light gray cabinet
- Accept custom design and special order

#### Standard :

- Manufactured by ISO 9001-2015 company
- Meet AIS requirements

#### Accessories :

- Cable tie, water proof connector and swell bolt
- Adapter, pigtail, splice tray and fusion sleeve as optional

#### Adapter Capacity :

- FC/SC/ST adapter type support 12 fibers
- LC (SCF) adapter type support 24 fibers

#### Dimensions :

- 262 W x 84 D x 160 H mm

#### Ordering Information :

P/N	Descriptions
ODFWIS12U	ODF Wall I/D Steel 12F (6-12F) Size 262x84x160 mm

# ODF MINI WALL MOUNT OUTDOOR 6-12 FIBERS



P/N : ODFWOS12U

#### Applications :

- Interface and distribute the fiber optical communication system

#### Features :

- Steel cabinet wall/pole mount for outdoor application
- Cabinet made from electro galvanize steel 1 mm thickness
- Combine splicing function, storing of fiber optical cable, patch cord and pigtail
- Store and protect excess optical cable and patch cord
- Support FC/SC/ST/LC adapter type with snap plate
- Splicing and distribution 12 fibers per mini-splice tray
- Nice shape, easy installment and maintenance
- Easily fixed by swell bolt or bolt, convenient for operation and inspection
- Provide strength member holder to fix the main fiber cable
- Light gray cabinet
- Accept custom design and special order

#### Standard :

- Manufactured by ISO 9001-2015 company
- Meet AIS requirements

#### Accessories :

- Cable tie and water proof connector
- Adapter, pigtail, splice tray and fusion sleeve as optional

#### Adapter Capacity :

- FC/SC/ST adapter type support 12 fibers
- LC (SCF) adapter type support 24 fibers

#### Dimensions :

- 308 W x 94 D x 206 H mm

#### Ordering Information :

P/N	Descriptions
ODFWOS12U	ODF Wall O/D Steel 12F (6-12F) Size 308x94x206 mm