

ODF WALL/POLE MOUNT OUTDOOR 168-312 FIBERS



P/N : ODFWOA168U

Applications :

- Interface and distribute the fiber optical communication system

Features :

- Aluminum Cabinet wall/pole mount for outdoor application
- Cabinet made from aluminum 2.0 mm thickness
- Combine splicing function, storing of fiber optical cable, patch cord and pigtail
- Store and protect excess optical cable and patch cord
- Support FC/SC/ST/LC adapter type with single snap plate
- Splicing and distribution 12 fibers or 24 fibers per tray
- Support fiber bending radius 30 mm
- Nice shape, easy installment and maintenance
- Easily fixed by bolt, convenient for operation and inspection
- Provide strength member holder to fix the main fiber cable
- Light gray cabinet
- Steel cabinet as optional
- Accept custom design and special order

Standard :

- Manufactured by ISO 9001-2015 company

Accessories :

- Cable tie, water proof connector
- Rear supporting bracket (without bolt)
- Adapter, pigtail, splice tray and fusion sleeve as optional

Dimensions :

- ODFWOA168U : 440 W x 157 D x 810 H mm
- ODFWOA240U : 440 W x 189 D x 810 H mm
- ODFWOA312U : 440 W x 225 D x 810 H mm

Adapter Capacity :

P/N	Dimensions (mm)			Maximum Fiber Cores	Snap Plate Type	Connector Type
	W	D	H			
ODFWOA168U	440	157	810	168F	Snap Plate 168 (168F)	FC/ST/SC/E2000
					Snap Plate 168 (336F)	LC Duplex SCF
ODFWOA240U	440	189	810	240F	Snap Plate 240 (240F)	FC/ST/SC/E2000
					Snap Plate 240 (480F)	LC Duplex SCF
ODFWOA312U	440	225	810	312F	Snap Plate 312 (312F)	FC/ST/SC/E2000
					Snap Plate 312 (624F)	LC Duplex SCF

Ordering Information :

P/N	Descriptions
ODFWOA168U	ODF Wall O/D AL 168F (120-168F) Size 440x157x810 mm
ODFWOA240U	ODF Wall O/D AL 240F (168-240F) Size 440x189x810 mm
ODFWOA312U	ODF Wall O/D AL 312F (240-312F) Size 440x225x810 mm